



Declaration of Performance
No. 101-2

1. Unambiguous ID code of the product type: **block glued laminated timber made from coniferous wood without preservative treatment**
2. Intended use: **structural work and bridges**
3. Manufacturer: **Mayr-Melnhof Holz Reuthe GmbH**
4. Authorized representative: **no external authorized representative**
5. System for assessing and verifying the constancy of performance: **System 1**
- 6.a) Harmonized standard: **EN 14080:2013**
Notified body: **No. 1359**
7. Performance declared:

Essential characteristics	Performance
Mechanical properties as	
modulus of elasticity bending strength compressive strength tensile strength shear strength	Mechanical properties of strength classes GL20h, GL24c, GL 24h, GL 24hs, GL 28c, GL 28h, GL 30c, GL30h The allocation of the construction products supplied to the individual strength classes can be taken from the accompanying documents.
Geometric data	widths ranging between 80 mm and 260 mm heights ranging between 100 mm and 2 400 mm lengths of up to 34 m The relevant product dimensions can be taken from the accompanying documents.
Bonding strength as	
bending strength of finger joints glue line integrity	as specified pursuant to EN 14080, Table 2 & 3 delamination test pursuant to EN 14080, Annex C, Method B
Durability of bonding strength as	
product	spruce (<i>Picea Abies</i>), larch (<i>Larix</i>) adhesive for finger-joints: MUF, EN 301-I-90-FJ-0,3-S adhesive for surface bonding: MUF, EN 301-I-90-GP-0,3-S adhesive for block glue line product 1 PRF, EN 301 I 90 GP 0.6M product 2 MUF, EN 301 I 90 GF 1.5M



Durability against biological attack as	
natural durability class against wood destroying fungi EN 350-2	5
Fire resistance as	
geometric data charring rate as	see „Geometric data“
- characteristic density - species	characteristic density of the relevant strength class spruce (<i>Picea Abies</i>), larch (<i>Larix</i>)
Reaction to fire as	
Reaction to fire class	D-s2, d0 pursuant to EN 14080, Table 11
Emission of formaldehyde as	
formaldehyde emission class	E 1
Release of other dangerous substances	
release of other dangerous substances	not relevant

The performance of the above product conforms to the performance declared. The above named manufacturer is exclusively responsible for preparing the Declaration of Performance in accordance with Regulation EU/305/2011.

Signed on behalf of the manufacturer and in his name by:

Mathias Simma
General Manager

.....

Reuthe 26.08.2019

 1359	
Mayr-Melnhof Holz Reuthe GmbH 15 1359 – CPR - 0623	
EN 14080:2013 Glued laminated timber made from conifere without preservative treatment to be used in buildings and bridges	
Mechanical properties and fire resistance as	
– geometric data	see delivery note
– strength class and characteristic density	GL20h, GL24hs GL24c, GL24h, GL 28c, GL28h, GL30c, GL 30h
– species	spruce (<i>Picea abies</i>) larch (<i>Larix</i>)
Bonding strength as	
– bending strength of finger joints	pursuant to EN 14080:2013
– glue line integrity	B
Reaction to fire	D-s2, d0
Emission of formaldehyde	E1
Durability of bonding strength as	
– species	spruce (<i>Picea abies</i>) larch (<i>Larix</i>)
– adhesive for the surface bonding between the lamellas	MUF, I GP90S
– adhesive for finger joints	MUF, I FJ90S
– adhesive for block joints	PRF, I GP90 0.6M MUF, I GP90 1.5M
Durability of other properties as	
– natural durability against wood destroying fungi	5