

In compliance with Regulation 305/2011/EU of the European Parliament and of the Council of 9 March 2011 (the Construction Products Regulation - CPR) this certificate applies to the construction product

MM – crosslam

according to the product specification listed in the current addendum to this certificate placed on the market by

Company

MAYR-MELNHOF HOLZ HOLDING AG

Turm-gasse 67

AT-8700 Leoben

and produced in the manufacturing plant

Mayr-Melnhof Holz Gaishorn GmbH

Gaishorn 182

AT-8783 Gaishorn am See

This certificate attests that all provisions concerning the assessment and verification of constancy of performance described in

ETA-09/0036, issued on 21.04.2023

and

EAD 130005-00-0304

under system 1 for the performance set out in the ETA are applied and that the factory production control conducted by the manufacturer is assessed to ensure the constancy of performance of the construction product.

CERTIFICATE OF CONSTANCY OF PERFORMANCE

Certificate number: 1359-CPR-0886

Date of first issue: 06.10.2015

Date of issuance: 17.06.2025

This certificate will remain valid as long as neither the ETA, the EAD, the construction product, the AVCP methods nor the manufacturing conditions in the plant are modified significantly, unless suspended or withdrawn by the notified product certification body.

For the validity of this certificate see www.holzfor-schung.at.



Dr. Andreas Neumüller
Authorised signatory



PD Gerhard Grüll
Head of the Certification Body

Addendum to certificate 1359-CPR-0886

Date of issuance: 17.06.2025

Scope of certification for the following products:

MM – crosslam

Solid wood slabs to be used as structural elements in building

Structure:	minimum 3-layers, layers arranged perpendicular (angle of 90°), maximum 13 layers, symmetrical construction
Strength classes of the laminations:	C 24
Thickness:	PUR: 36 - 280 mm MUF: 36 - 320 mm
Width x length	max. 4,0 x 18,0 m
Service classes:	1, 2
Wood species:	PCAB – Spruce / ABAL – Fir LADC – Larch
Adhesive:	
- Finger joints	Type I: PUR according to EN 15425
- Surface bonding	Type I: PUR according to EN 15425 (plant 4A) Type I: MUF according to EN 301 (plant 4B)