

In compliance with Regulation 305/2011/EU of the European Parliament and of the Council of 9 March 2011 (the Construction Products Regulation - CPR) this certificate applies to the construction product

MM - Crosslam

according to the product specification listed in the current addendum to this certificate placed on the market by

Company

MAYR-MELNHOF HOLZ GAISHORN GMBH

Gaishorn Nr. 182

AT-8783 Gaishorn

and produced in the manufacturing plant

AT-8783 Gaishorn, Gaishorn Nr. 182

This certificate attests that all provisions concerning the assessment and verification of constancy of performance described in

ETA - 09/0036, issued on 02.09.2020

and

EAD 130005-00-0304

under system 1 for the performance set out in the ETA are applied and that the factory production control conducted by the manufacturer is assessed to ensure the constancy of performance of the construction product.

CERTIFICATE OF CONSTANCY OF PERFORMANCE


Certificate number: 1359-CPR-0641

Date of first issue: 06.10.2015

Date of issuance: 01.12.2020

This certificate will remain valid as long as neither the ETA, the EAD, the construction product, the AVCP methods nor the manufacturing conditions in the plant are modified significantly, unless suspended or withdrawn by the notified product certification body.

For the validity of this certificate see www.holzforchung.at.



Dr. Andreas Neumüller
Authorised signatory



Dr. Manfred Brandstätter
Head of the Certification Body

Annex to Certificate 1359-CPR-0641

Date of issue: 01.12.2020

Scope of certification for the following products:

MM - Crosslam

Solid wood slabs to be used as structural elements in building

Structure:	at least 3-layer layers arranged perpendicular (angle of 90°) standard construction with 3, 5 and 7 layers
Thickness:	PUR: 36 - 280 mm MUF: 36 - 300 mm
Width x length	max. 4,0 x 18,0 m
Classes of utilisation :	1, 2
Wood species/strength class:	PCAB – Spruce/ABAL – Fir, LADC – Larch: C24/ T14
Adhesives:	Type I: MUF according EN 301 (plant 4A) Type I: PUR according EN 15425 (plant 4B)