



In compliance with Regulation 305/2011/EU of the European Parliament and of the Council of 9 March 2011 (the Construction Products Regulation - CPR) this certificate applies to the construction product

MM - crosslam

according to the product specification listed in the current addendum to this certificate placed on the market by

Company

MAYR-MELNHOF HOLZ HOLDING AG

Turmgasse 67 AT-8700 Leoben

and produced in the manufacturing plants

Mayr-Melnhof Holz Gaishorn GmbH

Gaishorn 182

AT-8783 Gaishorn am See

Mayr-Melnhof Holz Leoben GmbH

Turmgasse 67

AT-8700 Leoben

This certificate attests that all provisions concerning the assessment and verification of constancy of performance described in

ETA-09/0036, issued on 21.04.2023

and

EAD 130005-00-0304

under system 1 for the performance set out in the ETA are applied and that the factory production control conducted by the manufacturer is assessed to ensure the constancy of performance of the construction product.

CERTIFICATE OF CONSTANCY OF PERFORMANCE

Certificate number: 1359-CPR-0641 Date of first issue: 06.10.2015 Date of issuance: 10.05.2023

This certificate will remain valid as long as neither the ETA, the EAD, the construction product, the AVCP methods nor the manufacturing conditions in the plant are modified significantly, unless suspended or withdrawn by the notified product certification body.

For the validity of this certificate see www.holzforschung.at.

Tof the validity of this certificate see www.floiziorschang.at.

Dipl.-Ing. (BA) Eugen Spitaler

Authorised signatory



Dr. Manfred Brandstätter
Head of the Certification Body

HOLZFORSCHUNG AUSTRIA - ÖSTERREICHISCHE GESELLSCHAFT FÜR HOLZFÖRSCHUNG ZVR 850936522 A-1030 Wien, Franz-Grill-Straße 7 Tel +43-1/798 26 23-0 Fax +43-1/798 26 23-50 hfa@holzforschung.at www.holzforschung.at

Addendum to certificate 1359-CPR-0641

Date of issuance: 10.05.2023



Scope of certification for the following products:

MM - crosslam

Solid wood slabs to be used as structural elements in building

Structure: minimum 3-layers, layers arranged perpendicular

(angle of 90°),

maximum 13 layers, symmetrical construction

Strength classes of the laminations: C 24

Thickness: PUR: 36 - 360 mm

MUF: 36 - 320 mm¹

Width x length max. 4,0 x 18,0 m Service classes: 1, 2

Wood species: PCAB – Spruce / ABAL – Fir,

LADC - Larch1

Adhesive:

- Finger joints Type I: PUR according to EN 15425

Surface bonding Type I: MUF according to EN 301¹

Type I: PUR according to EN 15425

¹ applies only to the manufacturing plant in AT-8783 Gaishorn am See