Declaration of Performance

No. DOP MMHP BS 4978

1. Unique identifier code of the product type:

FSH-WPCA-SS-C24
FSH-WPCA-GS-C16
FSH-WPCA-SS-C24
FSH-WPCA-GS-C16

- 2. Application: building and bridges
- Manufacturer: Mayr-Melnhof Holz Paskov s.r.o. CZ-73943 Staric 54
 Authorised representative: no external authorised representative
- 5. System for assessment and verification of the reliability of performance:

System 2+

No. 1359

EN 14081-1:2005 + A1:2011

6.a) Harmonised standard:

Notified body:

7. Declared services:

Essential properties	Performance	
Mechanical properties as		
Modulus of elasticity	Mechanical properties of the strength classes for:	
Modulus of rupture	[FSH-WPCA-SS]: C24	
Compressive strength	[FSH-WPCA-GS]: C16	
Tensile strength	[FSH-WPCA-SS]: C24	
Lateral resistance	[FSH-WPCA-GS]: C16	
	according to EN 338	
Durability against biologica	l infestation as	
Natural durability class against wood-destroying fungi EN 350-2	For all product types: 5	
	according to EN 338	
Fire resistance as		
Geometric data	For all product types: see "Geometric data".	
Burning rate as		
specific density	For all product types: Specific bulk density of the respective strength class	
Type of wood	Refer to the accompanying documents to know the respective type of wood.	
Fire behaviour as	·	
Fire behaviour class	For all product types: D-s2, d0 according to EN 14081-1, Annex C	
Release of other hazardous materials		



Release of other hazardous	For all product types: not relevant
materials	

The performance of the above product is as declared. The manufacturer mentioned above is solely responsible for drawing up the declaration of performance in accordance with (EU) Regulation No. 305/2011.