Declaration of Performance

No. DOP MMHP DIN 4074

- 1. Unique identifier code of the product type: FSH-WPCA-S10-C24
- Application: building and bridges
 Manufacturer: Mayr-MeInhof Holz Paskov s.r.o. CZ-73943 Staric 54
 Authorised representative: no external authorised representative
 System for assessment and verification of the reliability of performance: System 2+

No. 1359

6.a) Harmonised standard: EN 14081-1:2005 + A1:2011

Notified body:

7. Declared services:

Essential properties	Performance
Mechanical properties as	
Modulus of elasticity	Mechanical properties of the strength classes for:
Modulus of rupture	[FSH-WPCA-S10]: C 24
Compressive strength	according to EN 338
Tensile strength	
Lateral resistance	
Durability against biological infestation as	
Natural durability class	For all product types: 5
against wood-destroying fungi EN 350-2	according to EN 338
Fire resistance as	
Geometric data	For all product types: see "Geometric data".
Burning rate as	
specific density	For all product types: Specific bulk density of the respective strength class
Type of wood	Refer to the accompanying documents to know the respective type of wood.
Fire behaviour as	
Fire behaviour class	For all product types: D-s2, d0 according to EN 14081-1, Annex C
Release of other hazardous materials	
Release of other hazardous materials	For all product types: not relevant

The performance of the above product is as declared. The manufacturer mentioned above is solely responsible for drawing up the declaration of performance in accordance with (EU) Regulation No. 305/2011.

Signed for and on behalf of the manufacturer by:

